



Grain weights are calculated by the amount of line out of the water in the "D" loop. The portion of a sink tip used on a regular line or on a Skagit system are not included in the recommended grain weights. SR recommendations are for two hand spey casting, subtract 60 grains for single hand casting.

### 2011 Rod / Line Weight Recommendations

Model	Length	Line	Grain Window	Skagit Compact & Skagit Float	Skagit Switch	Scandi Compact	Tactical Steelhead	Spey-dicator	Standard Floating
TR 5120	12' 0"	5	360-480	420	n/a	390	5	SD5	40+ WF8
TR 6126	12' 6"	6	420-540	480	n/a	450	6	SD6	Delta 6/7
TR 7130	13' 0"	7	510-620	570	n/a	540	7	SD7	Delta 7/8
TR 8136	13' 6"	8	570-680	630	n/a	n/a	8	SD8	Delta 8/9
TR 9140	14' 0"	9	630-750	660	n/a	n/a	9	SD9	Delta 9/10
TR 10150	15' 0"	10	700-800	720	n/a	n/a	n/a	n/a	Delta 10/11
SR 4106	10' 6"	4	210-270	n/a	n/a	240	n/a	SD4	WF6F
SR 5108	10' 8"	5	270-330	360	360	300	5	SD5	WF7F
SR 61010	10' 10"	6	330-390	390	390	360	6	SD6	WF8F
SR 71010	10' 10"	7	390-450	450	450	420	7	SD7	WF9F
SR 81010	10' 10"	8	450-510	510	510	480	8	SD8	WF10F
DH 4119	11' 9"	4	270-390	360	n/a	300	n/a	SD4	40+ WF6
DH 5122	12' 2"	5	330-450	390	n/a	360	5	SD5	40+ WF8
DH 6126	12' 6"	6	390-510	450	n/a	420	6	SD6	Delta 6/7
DH 7130	13' 0"	7	480-590	540	n/a	510	7	SD7	Delta 7/8
DH 8133	13' 3"	8	540-650	600	n/a	n/a	8	SD8	Delta 8/9
DH 9136	13' 6"	9	600-720	660	n/a	n/a	9	SD9	Delta 9/10
DH 7146	14' 6"	7	500-600	n/a	n/a	n/a	7	SD7	Delta 7/8
DH 8150	15' 0"	8	600-700	n/a	n/a	n/a	8	SD8	Delta 8/9
SOLO 6126	12' 6"	6	390-510	450	n/a	420	6	SD6	Delta 6/7
SOLO 7129	12' 9"	7	480-590	540	n/a	510	7	SD7	Delta 7/8
SOLO 8130	13' 0"	8	540-650	600	n/a	n/a	8	SD8	Delta 8/9

### Polyleader Specs

Type-Sink Rate	5' Length	8' Length	10' Length	14' Length
Float - 0" ips	16 grains	n/a	26 grains	40 grains
Hover - 0.5" ips	17 grains	24 grains	28 grains	n/a
Intermediate - 1.5" ips	18 grains	25 grains	30 grains	38 grains
Slow Sink - 2.6" ips	20 grains	26 grains	34 grains	n/a
Fast Sink - 3.9" ips	22 grains	30 grains	38 grains	52 grains
Super Fast Sink - 4.9" ips	36 grains	52 grains	56 grains	64 grains
Extra Super Fast - 6.1" ips	44 grains	78 grains	88 grains	112 grains

### Custom Cut Tip Specs

Size	Per Foot	Sink Rate	Length	Loop Color
CCT-T7	7 grains	7" ips	10' or 18'	White
CCT-T10	10 grains	10" ips	10' or 18'	Orange
CCT-T13	13 grains	13" ips	10' or 18'	Brown
CCT-T15	15 grains	15" ips	10' or 18'	Black
CCT 200	10 grains	10" ips	20' sink tip looped at both ends	
CCT 330	16 grains	16" ips		

### Running Line Diameter

Size	Float	Interm.
20lb Ridge	.036"	.033"
30lb Ridge	.040"	.037"
20lb Non-Ridge	.030"	n/a
Miracle Braid 30lb.	.028"	n/a

### 40 + Specs

Size	Grains	Head Lgth
WF5 Float	245	35'
WF6 Float	265	35'
WF7 Float	285	35'
WF8 Float	325	35'
WF9 Float	365	35'

### Multi-Tip Replacement Tips

Size	Loop Color	Type	Grains	Sink Rate	Length
6/7	Lt. Blue	Interm.	77 grains	1.5ips	13'
6/7	Lt. Blue	Type 3	77 grains	3ips	13'
6/7	Lt. Blue	Type 7	77 grains	7ips	13'
7/8	Lt. Green	Interm.	85 grains	1.5ips	13'
7/8	Lt. Green	Type 3	85 grains	3ips	13'
7/8	Lt. Green	Type 7	85 grains	7ips	13'
8/9	Orange	Interm.	97 grains	1.5ips	14'
8/9	Orange	Type 3	97 grains	3ips	14'
8/9	Orange	Type 7	97 grains	7ips	14'
9/10	Dk Green	Interm.	105 grains	1.5ips	15'
9/10	Dk Green	Type 3	105 grains	3ips	15'
9/10	Dk Green	Type 7	105 grains	7ips	15'
10/11	Blue	Interm.	115 grains	1.5ips	15'
10/11	Blue	Type 3	115 grains	3ips	15'
10/11	Blue	Type 7	115 grains	7ips	15'

**BalticFlyFisher**

Beekfeld 7

D-21255 Tostedt, Germany

+49 4182 291312 balticflyfisher.eu

11.01.2011